## For Use With MS-Series Proximity Readers



## **Standard Light Proximity Card**

- Wallet friendly thinner than other comparable proximity cards
- · Extremely durable
- · Industry standard formats
- Unique ID codes
- Lifetime Warranty



## MT-10X Multi Technology Proximity Card

- ISO thin, just 0.031" (0.8 mm)
- · Can also print bar codes
- Unique ID codes

Keri's KC-10X Standard Light Proximity Card provides maximum read range performance in a thin package that is easily carried in a wallet or purse or worn on clothing with a clip or lanyard. These cards are extremely durable and convenient. They are manufactured with a vertical hanging slot punch and they come with a lifetime warranty.

The MT-10X Multi Technology Proximity Card allows the user to combine several identification technologies in a single credit card thin credential. One of the most popular features of the Multi Technology Cards is that they can accept a direct print video image, typically a photograph, a bar code, and other graphics from most industry standard dye sublimation printers, to create a custom access credential.

The KC-10X Standard Light Card is recommended over the MT-10X Multi Technology Card whenever possible because of its lower cost and lifetime warranty. The Standard Light Cards can be fitted with PVC label or "skin" which can accept a direct printed image to provide photo ID at a much lower cost and greater durability.

Keri **Proximity Credentials** (including Cards, Tags, and Patches) can be used interchangeably on the same system without worry about ID code duplication or format matching.




### www.kerisys.com

302 Enzo Drive • San Jose, California 95138 • email: sales@kerisys.com Phone: 408-435-8400 • Toll Free: 800-260-5265 • Fax: 408-577-1792

# **MS-Series**<sup>™</sup> Proximity Cards

## DATA SHEET - Page 2 of 2

#### **KC-10X Standard Light Proximity Card**



## **Specifications:**

#### Read Range\*:

MS-3000 up to 4 inches (10 cm) MS-4000 up to 1 inch (2.5 cm) MS-5000 up to 8 inches (20 cm) MS-7000 up to 15 inches (38 cm)

#### Size:

L = 3.38, W = 2.14, T = 0.059 inches Approx.  $86 \times 54 \times 1.5$  mm

#### Weight:

0.31 oz (8.8 g)

#### **Material:**

**ABS** 

#### Frequency:

125 KHz excitation / 62.5 KHz return

#### **Temperature:**

-40° C to +70° C

#### **Humidity:**

0-100% non-condensing


#### Color:

Off white

#### Warranty:

The Standard Light Proximity Card comes with a limited lifetime warranty against defects in materials and workmanship.

#### MT-10X Multi Technology Proximity Card



#### **Specifications:**

### Read Range\*:

MS-3000 up to 3 inches (7.6 cm) MS-4000 up to 1 inch (2.5 cm) MS-5000 up to 4 inches (10 cm) MS-7000 up to 12 inches (30 cm)

#### Size:

L = 3.38, W = 2.14, T = 0.031 inches Approx.  $86 \times 54 \times .08$  mm

#### Weight:

0.19 oz (5.5 g)

#### Material:

PVC with a printable, gloss surface

#### Frequency:

125 KHz excitation / 62.5 KHz return

Note: Specifications subject to change without notice. Trademarks are the property of their respective owners.

#### **ORDERING INFORMATION:**

# Model NumberDescriptionKC-10XClamshell NXT Proximity Card for MS Readers

MT-10XP Thin Photo Imagable NXT Proximity Card for MS Readers
MT-10XM Thin Photo Imagable NXT Proximity Card with magnetic stripe for MS Readers

PKT-10X Proximity Key Tag for MS Readers



Presented By:

<sup>\*</sup> Read range is stated in a clean RF and electrical environment with card presented parallel to the reader surface.